Amendment dated: November 14, 2005 Reply to Office Action of June 14, 2005 Attorney Docket No.: 21295.0039

This listing of claims will replace all prior versions and listings of claims in this application:

a.) Listing of Claims

1. (Currently amended) A method for controlling analytical and adjustment operations of a microscope, comprising the following steps:

depicting a data set in graphical form on a display associated with the microscope; selecting at least one position in the graphical form of the data set that depicts an image of the specimen;

identifying automatically a region from the data set and the selected position; selecting an adjustment function for execution of an adjustment operation.

wherein the adjustment operation modifies at least one image sensing parameter and the image sensing parameters consist essentially of zoom, image centering.

detection sensitivity, illuminating light output, spectral composition of the illumination, polarization of the illumination, spectral detection of the identified region, and rotation of the identified region; and performing an analytical or adjustment operation or both on a structure of interest, wherein the analytical operation is based on the geometry of the structure of interest or on the data set of the structure of interest determined by means of pattern recognition; and

focusing automatically of a structure of interest within the identified image of the specimen.

- 2. (Canceled)
- 3. (Canceled)
- 4. (Canceled)
- 5. (Canceled)
- (Original) The method as defined in claim 1, comprising the steps:
 focusing automatically of a structure of interest within the identified image of the specimen; and

Amendment dated: November 14, 2005 Reply to Office Action of June 14, 2005 Attorney Docket No.: 21295.0039

centering the structure of interest within the image of the specimen.

7. (Currently amended) An arrangement for controlling analytical and adjustment operations of a microscope comprising:

multiple detectors for converting optical signals into electrical signals; an electronic acquisition system, which converts the electrical signals coming from the detectors into digital signals and preprocesses them, is provided;

a PC, which receives the digital signals from the electronic acquisition system and identifies from the digital signals a graphical depiction which corresponds to an image of the specimen;

a display, which reproduces the graphical depiction and moreover offers selectable adjustment functions to the user, is connected to the PC wherein the adjustment functions are selected for execution of an adjustment operation, wherein the adjustment operation modifies at least one image sensing parameter and the image sensing parameters consist essentially of zoom, image centering, detection sensitivity, illuminating light output, spectral composition of the illumination, polarization of the illumination, spectral detection of the identified region;

an input unit is provided for choosing the adjustment functions and selecting at least one structure of interest in the image of the specimen; and

an electronic control system, which receives information about geometry models identified by a pattern recognition process, with which electronic control system the adjusting elements of the microscope are to be controlled, is connected to the PC, wherein the arrangement is adapted to the automatic focusing of the structure of interest within an identified image of the specimen.

8. (Original) The arrangement as defined in claim 7, wherein the electronic control system has a memory that serves for temporary storage of the at least one structure of interest and is connected via a line to a routing unit; and a pixel clock is in communication both with the memory and with the routing unit.

Amendment dated: November 14, 2005 Reply to Office Action of June 14, 2005 Attorney Docket No.: 21295.0039

9. (Original) The arrangement as defined in claim 8, wherein the routing unit has multiple outputs by way of which the microscope is controllable.

HOUSTON ELISEEVA

- 10. (Original) The arrangement as defined in claim 7, wherein the electronic acquisition system has multiple analog/digital converters that are connected to an electronic circuit.
- 11. (Original) The arrangement as defined in claim 10, wherein the electronic circuit is configured as an FPGA.
- 12. (Original) The arrangement as defined in claim 7, wherein the adjustment functions are arranged on the display in a panel box in the form of multiple click buttons.
- 13. (Currently Amended) A software program on a data carrier for controlling analytical and adjustment operations of a microscope, wherein the following processes are carried out:

depicting a data set in graphical form on a display associated with the microscope; selecting at least one position in the graphical form of the data set that depicts the image of the specimen;

identifying automatically a region from the data set and the selected position; and selecting an adjustment function for execution of an adjustment operation wherein the adjustment operation modifies at least one image sensing parameter and the image sensing parameters consist essentially of zoom, image centering, detection sensitivity, illuminating light output, spectral composition of the illumination, polarization of the illumination, spectral detection of the identified region, and rotation of the identified region; and

Amendment dated: November 14, 2005 Reply to Office Action of June 14, 2005 Attorney Docket No.: 21295.0039

performing an analytical or adjustment operation or both on a structure of interest, wherein the analytical operation is based on the geometry of the structure of interest or on the data set of the structure of interest determined by means of pattern recognition.

automatic focusing of a structure of interest within the identified image of the

14. (Canceled)

specimen.

- 15. (Canceled)
- 16. (Canceled)
- 17. (Canceled)
- 18. (Original) The software program as defined in claim 13, comprising:
 automatic focusing of a structure of interest within the identified image of the specimen;

and centering of the structure of interest within the image of the specimen.